



## Main Features

- High-performance Stereo Amplifier by Bang & Olufsen ICEpower Technology (Bang & Olufsen ICEpower 50ASX2-SE)
- USB Audio Class2 High-speed Input from PC/Mac (Tenor 8802)
- 32bit/192kHz D/A Converter (BurrBrown PCM5102)
- Supports Asynchronous Transfer Mode
- Total 5 Inputs (USB, Coaxial, Optical, Line1, Line2)
- Motorized Volume Control
- No Cooling Fan for Silent Operation
- Detachable AC Socket
- Aluminium Front Panel and Volume Knob
- Approx 40% Power Saving compare to the previous similar class model (AG-H380)
- Remote Control (Also controls DS-H01)
- Available in Silver or Black

## General Specifications

- Output Power: 60W x 2 (4 ohms, 1kHz, less than 1% THD)  
30W x 2 (8 ohms, 1kHz, less than 1% THD)
- USB Input: x 1 (USB 2.0)
- Digital Audio Inputs: x 2 (Coaxial, Optical)
- Analogue Audio Inputs: x 2 (RCA)
- Subwoofer Preout: x 1 (RCA)
- Headphone Out: x 1 (6.3mm)
- Speaker Terminals: x 1 pair (Binding Post, AWG8-graded)
- Input Signal Sampling Rate: 44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz
- Frequency Response: 10Hz - 80kHz
- Signal-to-Noise Ratio: 100dB (Line Input, IHF-A/Input short)
- Total Harmonic Distortion: 0.05% (1kHz, 4 ohms)
- Operation: 120V AC, 60Hz (US), 230V AC, 50Hz (EUR)
- Power Consumption: 34 W
- Dimensions (W x H x D): 8-1/2" x 2-3/8" x 10-1/8"  
215 x 61 x 258 mm
- Weight: 3 lbs. 8 oz., 1.6 kg

